



303, Helix, Sayajigunj, Vadodara – 390 005. Phone: 0265-3011677

htc@hemtech.in

Model: HTC-6132

PAPER MOISTURE METER

Suitable for measuring moisture content of Craft paper, paper reel, waste paper bale, cartons, paper board,

corrugated rolls & Sheets, paper pallets, paper containers, paper tubes, paper cones, paper cores, etc

Specification:		1 1
Display	4 Digit 10mm LCD	
Moisture Range	0 – 50%	CONTACT MATERIAL PROPERTY AND ADDRESS OF THE PARTY AND ADDRESS OF THE P
Temp. Range	-10 to 60°C	
Resolution	0.1	
Accuracy	Moisture: ±(0.5%+1), Temperature: ±0.8%	
Accessories	Carrying case	
Aux. Supply:	4 x 1.5V AA Batteries	CONTRACTOR OF THE PARTY OF THE
Cabinet Size	178x68x39mm ABS Plastic	

Note:

Such Moisture Meters should be used for approximation only. They measure the electrical resistance between the contact points (probes), hence they will measure only the maximum moisture % at contact point. If you use any Flat Probe Type unit, it will show the Surface Moisture only. If your use any Pin Probe Type unit, it will show the maximum moisture across the point of penetration. It cannot show the MOISTURE CONTENT of the sample Paper / Board, etc. For such purpose either the Oven Method or dedicated MOISTURE BALANCE must be used.