

**Torque Tester** 











## **Motorised Torque Tester**

Torque Tester is useful for checking the quality of the Capping on the Bottles for Food as well as Pharmaceutical Industries.

Hemtech manufactures two version of Torque Testers :

1. HT-BCTT-M : Manual Torque tester

2. HT-BCTT-A : Advanced Motorised Torque Tester

Both the models offer in common following facilities:


Closing Torque Limit Alarm

- Closing Torque Limit Alarm
- Selectable units (kg-cm, N-m, Lbf-in)
- Calibration / Validation facility

As it offers excellent control over Torque Application, there is possibility of performing controlled test without opening the Cap. Hence it is very good tool for testing for test where in one wants to make sure that the cap is not opened at particular torque. Thus it can also be used as NON-DESTRUCTIVE Tester.



- Easy to use CONSOLE
- Multi-Line LCD display
- Indication LEDs.



## **Technical Specification:**

	/	HT-BCTTA10	HT-BCTTA20	HT-BCTTA30	HT-BCTTA50	HT-BCTTA100	HT-BCTTA200
Range		1.0000	2.0000	3.0000	5.0000	10.000	20.000
Resolution	N-m	0.0001	0.0001	0.0001	0.0001	0.001	0.001
Range	/	10.200	20.400	30.600	51.000	102.00	204.00
Resolution	Kg-cm	0.001	0.001	0.001	0.001	0.01	0.01
Range	1.1.	8.850	17.700	26.550	44.250	88.50	177.00
Resolution	Lb-in	0.001	0.001	0.001	0.001	0.01	0.01
Precision		+/- 0.5 %					
Sampling frequency		2000 Hz					
Power		Battery: 8.4 V DC (1.2V X 7 Ni-MH Battery bank) – rechargeable (charging time 6 hrs)					
		Adaptor: Input: 220V AC, 50 Hz Output: 10V DC, 300mA					
Speed		0.5 to 6 rpm					
Interface		RS 232					
Software		hemWIZARD					

Regd. Office: 484 / B / 2, GIDC Industrial Area, Makarpura, Vadodara - 390 010.

: +91-8000484484, 8238030484 Email: sales@hemtech.in

CIN: U31900GJ2009PTC056166